













6 Band Instructions © For 6, 6N, 6NX, 6T, 6TW2X, 6WA, 6WR, 61N, 6WB, 6WB-D, 6ML

It all began in the Middle East, a land of mystery and intrigue, with Sheiks, who while riding gaily decorated camels and spirited horses, ruled the desert with golden sceptres and gilded swords. This was the birthplace of the famed puzzle rings. Centuries ago these puzzle rings served as wedding bands, and were worn by women of nomadic tribes. The husband held the secrets of the rings. This guaranteed his wife's faithfulness, for the ring once removed from her fingers would fall apart.

					
<p>1. Hold Band stamped "1" (rounded outside band) with your left hand with the irregular portion of the band up.</p>	<p>2. Bring Band stamped "2" (other outside band) up against "1" band forming a diamond shape. Note - these are the outside bands when the ring is assembled.</p>	<p>3. Bring up the other two similarly shaped bands ("5" and "6") from the bottom so that they fit against the "1" and "2". Two bands ("3" and "4") should remain hanging underneath.</p>	<p>4. Grasp band stamped "4" in your right hand with the stamp facing you and the flat part of the band up, allowing the "1", "2", "5" and "6" bands to fall to one side. If you're right-handed you may want to transfer the "4" band to your left hand.</p>	<p>5. With your free hand take the band stamped "3" (it should be hanging at the bottom) by the flat part of the band and bring it up towards the "4" band until the bands are almost against one another.</p>	<p>6. Holding the "3" band between your thumb and forefinger, turn the band clockwise.</p>
					
<p>7. Continue turning until you have completed a 180-degree rotation.</p>	<p>8. The two bands should fit together locking in the 4 remaining bands. (1, 2, 5, and 6).</p>	<p>9. When you have completed the last step, if you turn the ring right side up the "3" and "4" bands should create an X.</p>	<p>10. Take the first band on the same side which is "6" and rotate the band until the irregular shaped part is on the inside of the ring.</p>	<p>11. Fold band up and fit against the "3". Be sure that the irregular shaped part fits over the remaining loose bands, if it isn't, the band won't fold down completely.</p>	<p>12. Flip ring over and start rotating "5" band until the irregular shaped part is on the inside of the ring.</p>




13. When you have completed the rotation, bring "5" band up against the three other bands, again being sure that the irregular shaped part fits over the remaining loose bands. Fold band up so that it fits against the "4".



14. Flip the whole ring over and start rotating the "2" band until the irregular shaped part is on the inside of the ring.



15. When you have completed the rotation, be sure that the irregular portion is over the remaining band, "1". Fold the band up against the "6" band.



16. Turn ring around and start rotating "1" band until the irregular shaped part is on the inside of the ring. You may have to loosen the other bands slightly to accomplish this.



17. The last two bands should fold into place.



18. Congratulations, you have assembled your ring.